

Viakon® Aerospace M22759/86 Hook Up Wire

Silver Plated Copper Conductor, 600 V

CME
wire and cable

A Viakable Company

Application

M22759/86 wires are normal weight, high performance aerospace hookup wires with a dual layer insulation of Polytetrafluoroethylene (PTFE)/Polyimide/PTFE tape covered with PTFE tape.

These conductors are used for internal equipment interconnections and to build harnesses for the aerospace industry.

Features

Excellent thermal stability and abrasion resistance.

Normal weight.

Specifications

M22759/86

SAE - AS22759/86

Voltage Rating:

- 600 volts

Temperature Rating:


- -55 °C to 200 °C

Engineering Information

1. Conductor: Stranded silver plated copper.

2. Insulation: Dual layer insulation of PTFE/Polyimide/PTFE tape.

3. Jacket: PTFE tape.



Technical Data

M22759/86 Normal Weight Silver Plated Copper Conductor

Part Number	Size AWG	Number of Strands	Size of Each Strand AWG	Conductor Diameter Minimum mil	Conductor Diameter Maximum mil	Final Product Operation: 600 V, 150 °C		
						Resistance Max @ 20 °C Ω/kft	Nominal O.D. Finished Cable mil	Nominal Weight lb/kft
M22759/86-26-*	26	19	38	17.5	19.4	38.40	35.0	1.42
M22759/86-24-*	24	19	36	22.5	24.4	24.30	40.0	2.04
M22759/86-22-*	22	19	34	28.5	30.4	15.10	45.0	2.90
M22759/86-20-*	20	19	32	36.5	38.4	9.19	53.0	4.48
M22759/86-18-*	18	19	30	45.5	48.4	5.79	63.0	6.65
M22759/86-16-*	16	19	29	51.5	54.4	4.52	70.5	8.50
M22759/86-14-*	14	19	27	64.5	68.4	2.88	83.5	12.90
M22759/86-12-*	12	37	28	83.5	87.4	1.90	102.5	19.70
M22759/86-10-*	10	37	26	106.0	110.0	1.19	125.0	30.80

*Color identification according to tables I and II (MIL-STD-681). Example: M22759/86-26-9, (9 = White).

MIL-STD-681 Color Code

Number	0	1	2	3	4	5	6	7	8	9
Color	Black	Brown	Red	Orange	Yellow	Green	Blue	Violet	Gray	White

This page intentionally left blank